

DVR Product Range

Standard configurations

To order call 0161 776 0888, or order online at www.quicksolutions.co.uk

		Platform	Case	Cams/ Audio	Storage	Export drive	Network storage	Display/ Capture FPS (Max)	CODEC	Hybrid (IP camera support) ¹	Monitor outputs	PTZ Control ²	USB Front/Rear	Removable hard drive	Remote viewing and control	Email alarm notification	Live audio chat	Warranty
Ultima Range	QS416- DV.D400	SBC Industrial	4U Rackmount	16/16	500GB- 3TB	DVD/RW	Yes	Live/400	MPEG4/ MJPEG	Yes	1xVGA 2xComposite ³	Yes	2/2	Yes	Yes	Yes	Yes	2 Years
	QS416- DV.D200	SBC Industrial	4U Rackmount	16/16	500GB- 3TB	DVD/RW	Yes	Live/200	MPEG4/ MJPEG	Yes	1xVGA 2xComposite ³	Yes	2/2	Yes	Yes	Yes	Yes	2 Years
	QS416- DV.D100	SBC Industrial	4U Rackmount	16/16	500GB- 3TB	DVD/RW	Yes	Live/100	MPEG4/ MJPEG	Yes	1xVGA 2xComposite ³	Yes	2/2	Yes	Yes	Yes	Yes	2 Years
	QS432- DV.H400	SBC Industrial	4U Rackmount	32/32	500GB- 3TB	DVD/RW	Yes	Live/400	MPEG4/ MJPEG	Yes	Expandable from 0 to 12	Yes	2/2	Yes	Yes	Yes	Yes	2 Years
Commercial Range	QS209- DVL.X50	Mother board	2U Rackmount	9/0	250GB- 1TB	DVD/RW	Yes	50/50	MPEG4/ MJPEG	Yes	1xVGA 1xComposite	Yes ⁴	2/2	No	Yes	Yes	Yes	2 Years
	QS216- DVL.X100	Mother board	2U Rackmount	16/0	500GB- 1TB	DVD/RW	Yes	100/100	MPEG4/ MJPEG	Yes	1xVGA 1xComposite	Yes ⁴	2/2	No	Yes	Yes	Yes	2 Years
	QS216- DVL.H200	Mother board	2U Rackmount	16/16	500GB- 1TB	DVD/RW	Yes	Live/200	MPEG4/ MJPEG	Yes	Expandable from 0 to 4	Yes ⁴	2/2	No	Yes	Yes	Yes	2 Years
	QS232- DVL.X200	Mother board	2U Rackmount	32/0	1TB	DVD-RW	Yes	200/200	MPEG4/ MJPEG	Yes	1xVGA 1xComposite	Yes ⁴	2/2	No	Yes	Yes	Yes	2 Years

OPTIONS (specify on order)	People counting	Remote Health Monitor	Automatic remote upgrades	Alarms In/Out	Additional Configurable Monitors	PTZ Keyboard support	RAID	Analogue audio channels	EPOS integration	MFD Control
Ultima	Yes	Yes	Yes	4/4	4/8/12	Up to 2	Yes	8-16	Yes ⁵	Yes
Commercial	Yes	Yes	Yes	4/4 ⁶	4 ⁷	No	No	No	No	No

¹ Please check list of supported IP cameras.

² Software-based control. See list of supported protocols.

³ 1x live rate spot output; 1x recorded rate spot output

⁴ Requires additional RS485-RS232 converter or alarm card.

⁵ EPOS integration is currently not available on 32 channel Ultima DVRs

⁶ 16 channel models only

⁷ .H200 model only

Together with our optional features, there are over 13,000 feature combinations to suit every type of installation.

Quick Solutions specialises in **simple**, **powerful** and **flexible** CCTV solutions. If none of the models shown here reflect your requirements, call our sales team on **0870 224 5647**.

Make/Model	Media Format	Resolution	Protocol	Default Port	Default User / Password	PTZ Support	Audio Support	Misc.
HTTP	JPEG	Any	HTTP	80	n/a	n/a	n/a	Any JPEG camera using HTTP protocol can record with this setting. URL of JPG image must be specified.
Acti	MPEG4	720x480(576), 352x240(288)	TCP / UDP Multicast	6000, 6001, 6002	Admin:123456	n/a	No (Under development)	
Arecont	JPEG	Any	TFTP/UDP/HTTP	69/80	n/a	N/a	n/a	
Axis 2130-R	JPEG	704x480, 352x240, 176x112, 704x240	HTTP	80	n/a	Yes	Yes	
Axis 211	JPEG / MPEG4 (simultaneous)	604x480, 320x240, 240x180, 160x120	HTTP (JPEG), RTP Unicast (MPEG4)	80 (JPEG), 554 (MPEG4 RTSP)	n/a	No	Yes	
Axis 213 PTZ	JPEG / MPEG4 (simultaneous)	4CIF (704x480), 2CIF Expanded (704x240), 2CIF (704x240), CIF (352x240), QCIF (176x120)	HTTP (JPEG), RTP Multicast (MPEG4)	80 (JPEG)	n/a	Yes	Yes	Decoder does not support 4CIF (640x480) MPEG4 stream
Axis 241QA	JPEG / MPEG4 (simultaneous)	4CIF (704x480), 2CIF Expanded (704x240), 2CIF (704x240), CIF (352x240), QCIF (176x120)	HTTP (JPEG), RTP Unicast (MPEG4)	80 (JPEG), 554 (MPEG4 RTSP)	n/a	No	Yes	
Axis (Others)	JPEG / MPEG4	Any	HTTP (JPEG), RTP Unicast/Multicast (MPEG4)	Varies	n/a	Yes (depending upon model)	Yes (depending upon model)	
Bosch	JPEG	Any	HTTP	80	n/a	No	n/a	Non-standard JPEG image, not supported by "Fast decompress" and AZTech CODEC
Canon	JPEG	320x240, 640x480	HTTP	80	n/a	Yes	n/a	
HikVision	H.264	QCIF, CIF, D1	TCP (Through SDK)	8000	n/a	No (Under development)	No (Under development)	Multiple channel is supported. Both major streams and sub streams are supported. In HD viewer, in order to
IQEye	JPEG	Any	HTTP	80	N/a	No	n/a	use sub stream, use camera number + 100 as channel number
JVC	JPEG	Any	HTTP	80	N/a	No	n/a	
Merit Lilin / Pixord	JPEG	Merit Lilin: Any Pixord: 704x576, 352x288	HTTP	80	N/a	Yes	n/a	Save preset not supported, you can only save preset using web interface
Messoa	JPEG	160x120, 640x480	HTTP	80	n/a	No	Yes (PCM, ADPCM)	
Panasonic NM100	JPEG or MPEG4 (not simultaneously)	640x480, 320x240, 160x120	HTTP (JPEG), RTP Unicast (MPEG4)	80	admin:password	Yes	n/a	
Panasonic NP1004, NP244	JPEG / MPEG4 (simultaneous)	1280x960 (JPEG only), 960x720 (JPEG only), 640x480, 320 x 240	HTTP (JPEG), RTP Unicast (MPEG4)	80(JPEG)	admin:12345	Yes	Yes	Set "Refresh interval(MPEG-4)" to 1 second if using MPEG-4 Max 8 simultaneous connections. Max 15FPS in JPEG full scan mode.
Panasonic NW47xS, NS32X, NP472	JPEG	640x480, 640x320, 320x240, 160x120	HTTP	80	admin: <empty>	Yes	n/a	Max 15 simultaneous connections PTZ is using digital pan/tilt, and will only work when zoomed in
Sanyo J2K	JPEG2000	720x480, 720x240, 640x480, 320x240, 160x120	HTTP	80	id1:1111 (Viewing) id2:2222 id3:3333 (Administrator) guest:guest (Viewing) admin:admin (Administrator)	No	n/a	JPEG2000 decoder does not work well with broken images and can cause memory leaks
Sanyo Pan Focus	JPEG	640x480, 720x240, 360x240, 180x120	HTTP	80	admin:admin (Administrator)	Yes	No (Under development)	The camera will stop functioning if two admin are logged in at the same time.
Sony	JPEG or MPEG4 (not simultaneously)	640x480, 384x288, 320x240, 256x192, 160x120	HTTP	80	admin:admin	Yes	Yes	
Toshiba IK-	JPEG	Any	HTTP	80	root:ikwb	Yes	Yes	

Make/Model	Media Format	Resolution	Protocol	Default Port	Default User / Password	PTZ Support	Audio Support	Misc.
WB21A								
Toshiba IK-WB02A/WR-01A	JPEG	Any	HTTP	80	n/a	No	Yes	Please use Messoa camera type
VivoTek	MPEG-4/JPEG	Up to 640x480	RTSP/HTTP	80	n/a	Yes (depending upon model)	No (Under development)	For streaming JPEG, use HTTP camera type with "/cgi-bin/video.jpg" as URL

Supported PTZ Protocols

Axis
 Bosch
 Canon VB-C50
 Dynacolor
 Kalatel
 LG SpeedDome
 Megapower matrix
 Merit Lilin (IP/Serial)
 Panasonic (various)
 Pelco CC1400/CM6700/CM6800
 Pelco D

Pelco Genex
 Pelco P
 Samsung
 Sanyo P95
 ScanDome
 Sensormatic RS-422
 SmartScan
 Sony RZ25
 Toshiba IK-WB21A
 VCL
 Vivotek PT7137

Quick Solutions

The Old School House
 Manchester Road
 Carrington
 Manchester
 M31 4UG

Tel: 0870 224 5647

Email: sales@quicksolutions.co.uk

www.quicksolutions.co.uk